



Waterproof



Dustproof



AC Mode



Wide Range
Temperature

- Designed with AC charging mode for convenient charging of electric vehicles (EV) and electric vehicle supply equipment (EVSE)
- Charge coupler compliant with SAE J1772
- Ergonomic design and impact resistant
- Mechanical Lifespan: Over 10,000 mating cycles



Charging System

32A Wall-Mounted EVSE

Applications



In Circuit Control Box (ICCB) Specification

Voltage	110V-240V	Enclosure	IP55
Charging Power	32A (240V)	Operation Temperature	-30°C to 50°C
Ground Monitoring	Supported	Certification	UL certified
Earth Fault Detection	Supported	NTC Function on Plug	Supported
Over Current Protection (OCP)	Supported	Weight	13kg (7.5M Coupler)
Product Dimension	208 mm x 327 mm x 100 mm	EV Charger Type Support	SAE Coupler
Auto-Recovery From Fault	15 min.	AC Plug Type	NEMA 14-50



Headquarters

BizLink Technology, Inc.

47211 Bayside Parkway, Fremont, CA 94538, USA
Phone +1 510 252 0786 sales@bizlinktech.com

Global Sales Contacts

USA sales@bizlinktech.com
Europe sales_europe@bizlinktech.com
China sales_gc@bizlinktech.com
India sales_india@bizlinktech.com

Japan sales_japan@bizlinktech.com
Malaysia sales_malaysia@bizlinktech.com
Taiwan sales_tw@bizlinktech.com